


Connecting the Terminal Block

Connect main supply (brown - Live, blue - Neutral) into terminal block making sure all connections are tight.



PENDANT LIGHT 22237



Please read instructions before commencing installation and retain for future reference.

SPECIFICATIONS

- **Material:** Aluminum - Acrylic
- **Lamp type:** LED , 64W , 3000K , 5760Lm , CRI 90
- **Ingress Protection:** IP20. Protection against entry of solid objects greater than 12mm in diameter.

INSTALLATION INSTRUCTIONS

- ⚠ Electrical products can cause death, injury, or damage to property. Maintenance and installation should only be carried out by a professional electrician.
- ⚠ The light source contained in this luminarie shall only be replaced by the manufacturer or his service agent or a similar qualified person.
- Ensure main supply is switched off.
- Insert masonry plugs into mounting surface (1).
- Fit mounting bracket onto mounting surface with self-tapping screws (2).
- Connect main supply wires to terminal block (3) making sure all connections are tight.
- Fit ceiling plate onto mounting bracket with smallest screws (4).
- Insert masonry plugs into mounting surface and screw the brackets (5).
- Fit the wire onto the smallest mounting brackets (6).
- Adjust the desired height and screw until to secure them (7).
- Reconnect power.

WARNING

- Make sure that the products is installed properly before connecting to electricity.
- Do not cover the fitting.
- Not for outdoor use or in wet conditions.

